

Reo-Pure™ water purification systems

Commercial RO Systems BLS 3000-9000 Series

MODELS AVAILABLE

- BLS 3000 (3000 gpd/2.0 gpm*)
- BLS 6000 (6000 gpd/4.1 gpm*)
- BLS 9000 (9000 gpd/6.3 gpm*)

BLS 3000 - 9000 RO SYSTEMS

- ◆ Energy Saving, High Flow Membrane Elements
- ◆ Stainless Steel Membrane Pressure Vessels
- ◆ High Pressure Booster Pumps
- ◆ 230V, 60Hz, 1-Phase
- ◆ Automatic Feed Water Shut-Off Valve
- ◆ 20" BB Sediment 5-Micron Pre-Filter
- ◆ Low Inlet Pressure Protection Switch
- ◆ System Operating Pressure Gauge
- ◆ Storage Tank Float Control Connection
- ◆ Pre-Treatment Lockout Connection
- ◆ 12 Month (One Year) Limited Warranty

Choose From Three Feature Packages To Fit Your Application

ECONO MODEL FEATURES

- ◆ Mini-Trol WQ Microprocessor Based Controller
- ◆ Fixed Reject Water Control (50%)
- ◆ Manual Membrane Flush
- ◆ Reject Water Recirculation Loop
- ◆ Pre-Treatment Lockout Connection

STANDARD MODEL FEATURES

- ◆ S-150 Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Manual Membrane Flush
- ◆ Product Water Check Valve
- ◆ Reject Water Recirculation Loop
- ◆ Pre-Treatment Lockout Connection

OPTIMUM MODEL FEATURES

- ◆ S-150 Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Automatic Membrane Flush
- ◆ Manual Feed Water Shut-Off Valve
- ◆ Post-Membrane Pressure Gauge
- ◆ Product Water Check Valve
- ◆ Reject Water Recirculation Loop
- ◆ Pre-Treatment Lockout Connection

Additional features available: Stainless Steel Pump and/or Frame, CIP (Clean-In-Place) Connection Ports, Product Water Pressure Switch with Relief Valve, 220V/50Hz/1-Phase, and others upon request.

** System production may vary depending upon incoming water temperature and chemistry. Based on feed water with 500 mg/L NaCl and temperature of 25°C. (77°F).*

