

Reo-Pure™ water purification systems

Commercial RO Systems BLS 400-2400 Series

MODELS AVAILABLE

- BLS 400 (400 gpd/0.28 gpm*)
- BLS 800 (800 gpd/0.56 gpm*)
- BLS 950 (950 gpd/0.66 gpm*)
- BLS 1900 (1900 gpd/1.32 gpm*)
- BLS 2400 (2400 gpd/1.67 gpm*)

BLS 400 - 2400 RO SYSTEMS

- ◆ Energy Saving, High Flow Membrane Elements
- ◆ Stainless Steel Membrane Pressure Vessels
- ◆ Brass Rotary Vane Pump
- ◆ 115V, 60Hz, 1-Phase
- ◆ Automatic Feed Water Shut-Off Solenoid Valve
- ◆ 20" SL Sediment 5-Micron Pre-Filter
- ◆ Low Inlet Pressure Protection Switch
- ◆ System Operating Pressure Gauge
- ◆ 12 Month (One Year) Limited Warranty

Choose From Three Feature Packages To Fit Your Application

ECONO MODEL FEATURES

- ◆ On/Off Control
- ◆ Fixed Reject Water Control (50%)
- ◆ Manual Membrane Flush
- ◆ Reject Water Recirculation Loop

STANDARD MODEL FEATURES

- ◆ Mini-Trol Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Manual Membrane Flush
- ◆ Storage Tank Float Control Connection
- ◆ Reject Water Recirculation Loop
- ◆ Product Water Check Valve
- ◆ Pre-Treatment Lockout Connection

OPTIMUM MODEL FEATURES

- ◆ Mini-Trol WQ Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Automatic Membrane Flush
- ◆ Storage Tank Float Control Connection
- ◆ Reject Water Recirculation Loop
- ◆ Product Water Check Valve
- ◆ Pre-Treatment Lockout Connection

Additional features available: Carbon Pre-Filter, Stainless Steel Pump and/or Frame, Product Water Pressure Switch with Relief Valve, 220V/50Hz/1Phase, and others upon request

** System production may vary depending upon incoming water temperature and chemistry.
Based on feed water with 500 mg/L NaCl and temperature of 25°C. (77°F).*

