

**Reo-Pure**™ water purification systems

# Commercial Wall Mount RO Systems

## WMS 400-2400 Series

### MODELS AVAILABLE

- WMS 400 (400 gpd/0.28 gpm\*)
- WMS 800 (800 gpd/0.56 gpm\*)
- WMS 950 (950 gpd/0.66 gpm\*)
- WMS 1900 (1900 gpd/1.32 gpm\*)
- WMS 2400 (2400 gpd/1.67 gpm\*)

### WMS 400 - 2400 RO SYSTEMS

- ◆ Energy Saving, High Flow Membrane Elements
- ◆ Stainless Steel Membrane Pressure Vessels
- ◆ Brass Rotary Vane Pump
- ◆ 115V, 60Hz, 1-Phase
- ◆ Automatic Feed Water Shut-Off Valve
- ◆ 20" SL 5-Micron Sediment Pre-Filter
- ◆ Low Inlet Pressure Protection Switch
- ◆ System Operating Pressure Gauge
- ◆ 12 Month (One Year) Limited Warranty

## Choose From Three Feature Packages To Fit Your Application

### ECONO MODEL FEATURES

- ◆ On/Off Control
- ◆ Fixed Reject Water Control (50%)
- ◆ Manual Membrane Flush
- ◆ Reject Water Recirculation Loop

### STANDARD MODEL FEATURES

- ◆ Mini-Trol Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Manual Membrane Flush
- ◆ Storage Tank Float Control Connection
- ◆ Reject Water Recirculation Loop
- ◆ Product Water Check Valve
- ◆ Pre-Treatment Lockout Connection

### OPTIMUM MODEL FEATURES

- ◆ Mini-Trol WQ Microprocessor Based Controller
- ◆ Inlet & Outlet Pre-Filter Gauges
- ◆ Adjustable Reject Water Control Valve
- ◆ Product & Reject Water Flow Meters
- ◆ Automatic Membrane Flush
- ◆ Storage Tank Float Control Connection
- ◆ Reject Water Recirculation Loop
- ◆ Product Water Check Valve
- ◆ Pre-Treatment Lockout Connection

*Additional features available: Carbon Pre-Filter, Stainless Steel Pump and/or Frame, Product Water Pressure Switch with Relief Valve, 220V/50Hz/1-Phase, and others upon request.*

*\* System production may vary depending upon incoming water temperature and chemistry. Based on feed water with 500 mg/L NaCl and temperature of 25°C. (77°F).*